

# ProfiMaster, two exhaust arms

- » Two exhaust arms
- » High capacity filter



## Applications

- » Low to medium levels of smoke and dust
- » Occasional to frequent use
- » For two work places

## Properties

- » Exhaust arm up to 4 m
- » Automatic Start/Stop (optional)
- » Rotating exhaust hood

## Benefits

- » Safe operation by rotation field control
- » Maintenance door allows easy filter change
- » Exhaust arm requires less adjustment due to exhaust hood design
- » Increased safety due to filter monitoring
- » Space-saving solution due to two extraction arms
- » Possibility of working in two alternating places due to dampers in the extraction hood

---

## Technical Data

<b>Filter</b>	
Filter stages	2
Filter method	Disposable filter
Filter surface	ca. 17 m <sup>2</sup>
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filter efficiency	> 99.5 %
Filterclass	E12
Additional filters	Pre-filter
<b>Basic data</b>	
Extraction capacity	2 x 700 m <sup>3</sup> /h
Dimensions (w x d x h)	785 x 730 x 950 mm
Weight	113.8 kg
Motor power	1.1 kW
Power supply	3 x 400 V / 50 Hz
Rated current	2.3 A
Noise level	72 dB(A)
<b>Additional information</b>	
Fan type	Radial fan