

S 145E

Vacuum unit with automatic filters cleaning



Technical data

- **Weight:** Kg 13
- **Max. tool power:** Watt 1x2400
- **Depression:** mm H₂O 2000
- **Noise:** dB(A) 67
- **Max. capacity:** m³/h 200
- **Filter surface:** m² 1
- **Absorbed power:** 1x1200
- **Container volume:** 45

Characteristics

- TUV certificate
- Extremely quiet
- Mobile units for extracting dust from grinding and various types of industrial work, fitted for connection to an electric tool
- Also suitable for fluid extraction
- S.C.S. Self Cleaning System with filter cartridgeS RUPES patent.
- M.I.C. Multifunction Intelligent Control: manual or automatic start-up, speed control, liquid-level indicator, working-time memory and service-interval indicator for replacement of motor brushes
- 2 generously-proportioned filter units for constant and high-quality filtering capacity
- Electrostatic charge dispersion device
- Large dust and liquid container, with generous rear space for cables and Pivotal front connector for hoses, Ø 25 - 29 - 38 - 50 mm
- S 145EL extractor, protection class L (EN60335-2-69/A2), suitable for dust with maximum tolerated exposure value >1.0 mg/m³
- Suitable for all type of work on surfaces with power tools – bodywork – wood – plastic
- Also find application in the building sector for combination with wet and dry diamond cutting and boring tools, and with general extraction of work residues